

8000D Blockout

Media Type	Label	✓	Adhesive Type	Permanent	✓
	Receipt			Removable	
	Tag			No Adhesive	
	Wristband		Environment	Indoor	✓
Material Type	Paper	✓		Outdoor	
	Synthetic		Properties	Cold Temperature	✓
Printing Technology	Direct Thermal (no Ribbon Required)	✓		Deep Freeze	
	Thermal Transfer (Ribbon Required)			High Temperature	
Finish	Matte	✓		Ultra High Temperature	
	Gloss			High Tack	
			Chemical Resistance	-	

Note: 8000D Blockout is not recommended for applications involving long term exposure to sunlight or extreme heat.

Additional Features

- No ribbon required for direct thermal printing, therefore only one stock item needed
- Black adhesive provides a 'blockout' to cover up any previous printed data
- Adhesive has a good initial tack and good ultimate adhesion to a wide variety of surfaces
- Produces good quality high contrast black images

Suggested Applications

- Price labelling or markdown to cover previous price
- Re-marking of boxes
- Product identification
- Latex free adhesive

Technical Specifications

	Description	Caliper
Facestock	Matte white uncoated thermal imaging paper	80 microns
Adhesive	Permanent acrylic adhesive	20 microns
Liner	62gsm glassine liner	54 microns
	Total	154 microns ±10%



Recommended Zebra Printers:	Mobile, desktop, mid-range and high-performance thermal printers
Minimum Application Temperature: When the label is applied, the environment and surface should be above this temperature	5°C
Service Temperature Range: Following correct application and appropriate dwell time (usually 24hrs) the media will withstand this temperature range	-20°C to 70°C
Recommended Storage Conditions: Storage of product before use	6 months duration when stored at 20°C to 24°C at 50% RH
Expected Life Span in Application: Following correct application and appropriate dwell time (usually 24hrs) we expect, but do not warrant, a life span as indicated	Indoor use, up to 1 year

Product Performance and Suitability

The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

For testing of this material, please order sample roll SAMPLE65464.